

Controller Design Based on ISE Minimization and Dominant Pole Retention Method

S. K. Agrawal^{1*}, Dinesh Chandra & Irfan Ali Khan

S.K.Agrawal

Lucknow Institute of Technology and Management
Lucknow, India

Dinesh Chandra

Motilal Nehru Institute of Technology,
Allahabad, India

Irfan Ali Khan

Integral University,
Lucknow, India

Abstract— A computer based method to reduce the complexity of the higher order controller, based on the minimization of integral square error (ISE) and Dominant Pole Retention method pertaining to unit step input is presented in this paper. In this order-reduction technique, dominant pole of the higher order plant is retained and reduced order model of the plant is obtained using ISE Minimization Technique. Using this reduced order plant a reduced order controller is obtained. The method has built in stability – preserving feature.

Keywords- Controller Design, Dominant Pole, ISE

I. INTRODUCTION

The simulation and design of controllers for higher-order systems is a difficult problem. The cost and complexity of the controller increases as the system order goes high. This problem can be overcome if a “good” reduced-order model is available for the original higher-order system and if it is possible to design a controller using a lower-order model, which will stabilize the original higher-order system when placed in the closed loop. Hence, for cost and time saving in design, and for simplifying implementation, reduced-order models are highly desirable for engineers in analysis, synthesis and simulation of complicated higher-order systems [1].

A review of concepts and approaches for controller reduction has been presented by Anderson and Liu [2]. Basically, the approaches can be divided into direct and indirect ones [3]: direct methods seek to obtain a low-order controller directly [4] in which, generally, a quadratic optimization problem is posed with an order constraint and a closed loop stability constraint; indirect methods are two types [5]: (a) a high-order controller can be derived from the assigned high-order plant, by using some LQG or H^∞ design method, and then an approximation of the controller is obtained, and (b) a low-order plant can be computed from the original one, and then a low-order controller is designed to be used with the original plant.

In [2], indirect strategies of type (a) using the methods of balanced realization [6, 7, 8], Hankel norm optimal

approximation [2,9,10], and q-covariance equivalent realization [11, 12] have been discussed. In their usual form, these techniques replace one stable high-order model by a second stable low-order model that usually is not an optimal L_∞ approximation; further, usually no frequency weighting is employed [2]. However, some frequency weighted versions of the first two methods are available [13].

In the following, the indirect strategy of type (b) is used to design a low-order controller. The plant is first approximated by a low-order model using the Integral Square Error Minimization Technique[14] and Dominant Pole Retention method. Integral Square Error was calculated with the help of Luss-Jakola Algorithm [15, 16]. The controller is then designed for this low-order plant and attached to the original plant.

II. BACKGROUND

Consider the control system [17] as shown in Fig. 1. Given $G_n(s)$ and $H(s)$, the problem is to derive the transfer function of the controller $C_f(s)$ which yields the desired response of the closed loop system. A classical approach to the design of the controller $C_f(s)$ is to specify the desired (also called reference) closed loop transfer function $G_{ref}(s)$, equate it to the closed-loop transfer function, and solve for the controller [17].

The overall closed-loop transfer function in Fig. 1 is

$$G_{ooo}(s) = \frac{C_f(s)G_n(s)}{1 + C_f(s)G_n(s)H(s)} = G_{ref}(s) \quad (1)$$